

# TECHNICAL PROPERTY

Style	HD425SI
Standard	ENISO 20345:2004 S1P
Reference	Rigger
Sole - Last	Groove - 500DIN
Size Range	36 ( 3 ) - 48 ( 13 )



Components	Material
Upper Leather	Full Grain Buffalo Haircell Leather S1 ( min.1.8 mm ) ( Golden tan colour )
Vamp Lining	Non-woven Felt ( Diddi & Gori )
Quarter Lining	None
Counter Lining	Non-woven Textile ( Abrasion resistant ) ( Aqualine )
Toe Cap	Steel Toe cap ( resistant to 200 J )
Inner Midsole	Steel Plate ( for penetration resistance to 1100N )
Stiffener	Thermoplastic board ( min. 1.6 mm )
Threads	Polyester ( Coats )
Fastening	Leather pull loops at both sides
Insole Board	Bonded fibre board - Antistatic, sweat absorber, antibacterial
Footbed	Full / Detachable, Non-woven Textile coated Felt
CE Label	ENISO 20345:2004 G500-02 S1 P
Inner Box	P70 Shoe Box
Box End Label	to be stucked to the inner box
<b>SOLE PROPERTY</b>	
Technology	Direct Injection and Moulded - Double Density
Midsole	Polyurethane ( Beige colour )
Outsole	Polyurethane ( Light beige colour )
Bumb Cap	Polyurethane ( Beige colour )
Antistatic Footwear	
Shock Absorber Heel	
Oil Resistant Outsole	
Slip Resistant Outsole	
Heat Resistant Outsole up to 110 °C	